



Small-scale Biomass Heating in an Urban Environment

Workshop on Smart Cities: Integrating Renewable Heating & Cooling Christoph Schmidl

Brussels, 9 February 2011







Content

- Framework Conditions
 - Renewable heat
 - Small scale biomass heating
- Role of small scale biomass heating in urban environments
- Special requirements
- Biomass solutions
- R&D needs
- Conclusions








Framework conditions - Renewable heat

- Bioenergy most relevant renewable energy source
- Bioheat most relevant application of bioenergy
- Residential heating most relevant bioheat application
- Residential heating –
 biggest absolute potential to contribute to 20/20/20 goals



Source: Sanner, Burkhard; Bilbao 2010







Framework conditions – Small scale biomass heating

■ Biomass for household energy ~ 200 Mm³ = 35 Mtoe (excl. DH)

■ Target for 2020: > 400 Mm³ = 70 Mtoe

■ 86% of household energy consumption used for heat

Biomass covers 97% of renewable heat market

Market: small scale combustion systems:

Appliance	Stock	Sales
Fireplaces	30 Mio.	1.7 Mio.
Stoves	25 Mio.	1.3 Mio.
Cookers	7.5 Mio.	0.5 Mio.
Boilers	8 Mio.	0.3 Mio.

Sources:

European Biomass Statistics, AEBIOM 2010, Reference year: 2007

Working Paper, Bio Intelligence Service, 2009







Roles of small-scale biomass heating in urban environments

- Central heating system for single dwellings
 - If no district heating is available
 - Replacement of fossil fuel heating systems
 - New buildings
- Object heating system
 - Central heating system for residential and office buildings
- Additional heating / Well-being / Aesthetic aspects ("lifestyle")
- Decentralised electricity production (Micro-CHP)







Special heating system requirements in urban environments

- Ultra-low emissions (air quality issues, e.g. PM)
- Compact units (limited space)
- Low heat output (energy standard of buildings, EPBD)
- User convenience
 - Automatic operation
 - Fuel availability ("home delivery service")
- Well-being effects (flame optics, radiation heat)
- High operating reliability (if used as main heating system)







Small scale biomass heating solutions on the market or under development...

Compact central heating solutions:

"PelletUnit" (7-15 kW) in modern leather design



www.eta.co.at

"Therm" (2-7 kW) for wall mounting



www.guntamatic.com







Innovative solutions for logwood stoves

- Simulation based design (CFD)
- Automatic airflow control system
- Automatic briquette stove
- Integration of secondary


www.rika.at technologies



Brussels, 9 February 2011 Folie 8



www.hapero.com









www.spartherm.com



Competence Centers for Excellent Technologies





Ultra-low emissions / Low heat output

Calimax Twist (1.8 – 6 kW)

www.calimax.com

Pellet boiler for the living room

Water/Room: 80/20

Emissions:

CO: 3mg/MJ

PM: 7mg/MJ

HC: 1mg/MJ

Efficiency:

 $\eta = 95\%$










Ultra high efficiency

- Condensing pellet boiler
- Efficiency > 100%



www.pelletsheizung.at








Compact integrated solutions


Pellets boiler + Thermal storage combination

Optimised for combination with solar thermal





www.pelletsheizung.at











Low heat output / well being / radiation heat


Ceramic inserts

Modular ceramic heat storage system

Tile casing (hypocaust)

■ Heat output: 2 – 6 kW (8-12h)







www.ortner-cc.at







Aesthetic aspects (lifestyle) / well being


Modular tile stove system as

- main heating
- additional heating
- design element






Micro-CHP: Steam Piston Engine (Demonstrator)



Generator:	Steam piston engine with integrated linear-generator
Fuel:	Woodpellets
Heat / Electric power	5-16 kW / 0.3-2kW
Electric Efficiency:	11 %
Total Efficiency:	> 90 %









Micro-CHP: Thermoelectrics (Prototype)


Pellet stove/boiler equipped with TEG

Heat output: 10 kW

Nominal electric power: 200 - 400 W


Thermogenerator

Thermoelectric Module















Research and development needs...

- Increase annual efficiency of heating systems >85-90%
- Zero-emission technology (i.p. logwood)
 - Supported by standards and legislation (e.g. Ecodesign Directive: Emission thresholds and Eco-Labelling of EUP)
- Lowest load systems (part load < 1 kW)</p>
- Combination of all HVAC technologies in one system
- Micro-CHP technology
 - Technology development / Increase of reliability
- New thermal storage solutions (e.g. PCM)








Conclusions

- Small-scale biomass heating is the leading technology for achieving Europe's 2020 Energy goals
- Several applications in urban environments
 - Main heating system
 - Additional heating / Well-being
 - Decentralised electricity production
- Innovative solutions already enter the market or are under development
- Further R&D and supporting legal and funding framework are necessary to make renewable industries' vision become reality!









Thank you for your attention!



Christoph Schmidl

Senior Researcher & Head of Unit Small-scale Combustion Systems BIOENERGY 2020+ Location Wieselburg Tel: +43 7416 52238 24

christoph.schmidl@bioenergy2020.eu

